


# SHUMAN Dyna-Purge

## Product Selection Guide

Dyna-Purge® offers a broad range of products to service your purging needs. Find your application and processing temperatures below, and identify the best product(s) for use. For a **free sample** or additional assistance, please contact your Dyna-Purge representative.

Processing Temperature	Injection	Extrusion	Dyna-Purge Product
320° F – 625° F (160° C – 329° C)	Cold and hot runners	Profile, sheet, blown and cast film, compounding, and blow molding	<b>F2</b>  Broad temperature range, versatile, low residue formula
320° F – 625° F (160° C – 329° C)	Cold and hot runners	Profile, sheet, cast film, compounding and blow molding	<b>D2</b> Broad temperature range, versatile, extra-scrubbing formula *
575° F – 715° F (302° C – 379° C)	Cold and hot runners	Profile, sheet, cast film, and compounding	<b>E2</b> High temperature range, engineering resin specific formula
380° F – 590° F (193° C – 310° C)	Cold and hot runners	Profile, sheet, cast film, compounding, and blow molding	<b>C</b> Broad Temperature range, clear and transparent resin specific, low residue formula
320° F – 500° F (160° C – 260° C)	Cold and hot runners	Profile, sheet, cast film, compounding, and blow molding	<b>A</b> PP, TPO and Low temperature range specific formula
290° F – 550° F (143° C – 287° C)	Cold and hot runners	Profile, sheet, cast film and compounding	<b>K</b> Low temperature range, low durometer specific formula *

\* MINIMUM CLEARANCE: 0.025 IN / 0.65 MM

Request your  
**FREE SAMPLE**  
Today

# Discover the Difference

For over 35 years, Dyna-Purge has led the industry in saving processors time and money with our high-performance engineered purging compounds.



## Take advantage of our ...

- ✔ **Versatility**  
Products to match every process and resin.
- ✔ **Productivity**  
Cleans on the first pass, minimizing downtime and reducing scrap.
- ✔ **Efficiency**  
Only small amounts required. No soaking or mixing. Unlimited shelf life. No hidden costs!
- ✔ **Service**  
Outstanding "factory-direct service" and technical support.
- ✔ **Safety**  
FDA, REACH, and RoHS compliant, non-abrasive, non-chemical formulas are safe for operator, machine, and the environment.



Shuman Plastics, Inc. | 35 Neoga Street | Depew (Buffalo), NY 14043 | (716)685-2121 | [www.dynapurge.com](http://www.dynapurge.com)

Dyna-Purge® is a registered trademark of Shuman Plastics, Inc.