



Productivity begins with purging®

Product Information:

Dyna-Purge® D2

*Improved “dual action” cleaning
versatile application range, broad spectrum use.*

Applications:	Injection- cold and hot runners Extrusion- profile, sheet, blown & cast film, compounding, and blow molding
Temperature Range:	320° F - 625° F (160° C - 329° C)
Types of Resins:	All
Minimum Clearance:	No restrictions
Amount of Purge:	1 to 2 times barrel capacity (actual amount needed depends upon machine conditions)

Dyna-Purge D2:

High performance, engineered grade incorporating our exclusive ‘3X’ technology. This dynamic product acts on the process boundary layers as well as negative flow and stagnation points. Its unique formula allows it to safely remove resin, color, carbon, additives and impurities without abrasives or chemicals.

Features & Benefits:

- Designed for quick color changes, resin changes, preventative machine maintenance and prior to manual cleaning
- Recyclable
- Easy to use- no process adjustment, mixing or soaking required
- Safe, non-hazardous ingredients are FDA compliant
- Heat stable- recommended during shutdown and start-up
- Economical- low “cost-per-purge”- small quantity needed to be effective
- Unlimited shelf life

***Please refer to “Suggested Purging Procedures” for processing information
and “Product Selection Guide” for additional products.***

Important! The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true to the best of our knowledge. NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SUITABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling or storage. Other factors may involve other or additional safety or performance considerations. While our technical personnel can respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State or local laws.

Dyna-Purge® is a registered trademark of Shuman Plastics, Inc.

35 Neoga Street • Depew, New York 14043, USA • Phone 716-685-2121 • Fax 716-685-3236 • info@dynamapurge.com • www.dynamapurge.com