



Productivity begins with purging®

Product Information:

Dyna-Purge® RF

Designed for pre-purge before screw pulls

Applications:	Extrusion- profile, sheet, blown and cast film, compounding Screw Pulls- extrusion or injection
Temperature Range:	275° F - 450° F (135° C - 232° C)
Types of Resins:	All
Minimum Clearance:	No Restrictions
Amount of Purge:	1 to 2 times barrel capacity (actual amount needed depends upon machine conditions)

Dyna-Purge RF:

The latest technology advancement allowing for effective cleaning of the barrel, screw and die. Self-releasing feature enables screw pulls and material removal from the metal surface. Scrubbing and pressurizing agents allow the purge to reach stagnation points.

Features & Benefits:

- Developed for color changes, resin changes, preventative maintenance, and prior to manual cleaning
- Excellent pre-purge before removing the screw
- Effective at low temperatures
- Recyclable
- Safe, non-hazardous, non-chemical ingredients are FDA compliant
- Heat stable- recommended during shutdown and start-up
- Economical low “cost-per-purge”- small quantity needed to be effective
- Easy to use- no processing adjustments, mixing or soaking required
- Low affinity for metal surfaces – easy removal.
- Unlimited shelf life

Please refer to “Suggested Purging Procedures” for processing information and “Product Selection Guide” for additional products.

Important! The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true to the best of our knowledge. NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SUITABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling or storage. Other factors may involve other or additional safety or performance considerations. While our technical personnel can respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State or local laws.

Dyna-Purge® is a registered trademark of Shuman Plastics, Inc.

35 Neoga Street • Depew, New York 14043, USA • Phone 716-685-2121 • Fax 716-685-3236 • info@dynamapurge.com • www.dynamapurge.com